NSN 5945-00-889-9948

Electrical Solenoid - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-889-9948

Thread Class:
2b mounting facility hole
Body Style:
Cylindrical frame
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.187 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.000 inches
Body Length:
4.030 inches
Case Material:
Steel
Case Surface Treatment:
Cadmium
Environmental Protection:
Dustproof and explosion proof
Fragility Factor:
Moderately rugged
Inclosure Type:
Fully enclosed
Magnetic Coil Quantity:
Magnetic Coil Quantity: 1
1
1 Duty Type:
1 Duty Type: Continuous
1 Duty Type: Continuous Terminal Location:
Duty Type: Continuous Terminal Location: Circumference
Duty Type: Continuous Terminal Location: Circumference Voltage Rating In Volts:
Duty Type: Continuous Terminal Location: Circumference Voltage Rating In Volts: 28.0 dc
Duty Type: Continuous Terminal Location: Circumference Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity:
Duty Type: Continuous Terminal Location: Circumference Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 4 threaded hole
Duty Type: Continuous Terminal Location: Circumference Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 4 threaded hole Current Rating:
Duty Type: Continuous Terminal Location: Circumference Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 4 threaded hole Current Rating: 4.4 amperes
Duty Type: Continuous Terminal Location: Circumference Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 4 threaded hole Current Rating: 4.4 amperes Storage Type:
Duty Type: Continuous Terminal Location: Circumference Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 4 threaded hole Current Rating: 4.4 amperes Storage Type: General purpose warehouse
Duty Type: Continuous Terminal Location: Circumference Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 4 threaded hole Current Rating: 4.4 amperes Storage Type: General purpose warehouse Actuator Stroke Type:
Duty Type: Continuous Terminal Location: Circumference Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 4 threaded hole Current Rating: 4.4 amperes Storage Type: General purpose warehouse Actuator Stroke Type: Pull
Duty Type: Continuous Terminal Location: Circumference Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 4 threaded hole Current Rating: 4.4 amperes Storage Type: General purpose warehouse Actuator Stroke Type: Pull Linear Force Delivered:
Duty Type: Continuous Terminal Location: Circumference Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 4 threaded hole Current Rating: 4.4 amperes Storage Type: General purpose warehouse Actuator Stroke Type: Pull Linear Force Delivered: 4.50 pounds

0.375 inches

NSN 5945-00-889-9948

Electrical Solenoid - Page 2 of 2



Power Takeoff Connection Hole Diameter:

Between 0.100 inches and 0.106 inches

Thread Size:

0.190 inches mounting facility hole

Mounting Facility Pattern:

Four position rectangular

Thread Series Designator:

Unf mounting facility hole

Terminal Type And Quantity:

4 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A134a0