NSN 5945-00-900-4786

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-900-4786

2.750 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.375 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility

Overall Height:

4.680 inches

Overall Width:

1.500 inches

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.173 inches single mounting facility

Frequency In Hertz:

60.0

Winding Quantity:

Coil Quantity:

Winding Dc Resistance Rating:

190.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Current Rating And Type:

125.0 milliamperes ac single winding

Time Delay:

0.075 seconds adjustable release time and 10.00 seconds adjustable release time

Operating Voltage Rating And Type At Specificationified Temp:

110.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load and 10.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 26.0 dc

Terminal Type And Quantity:

8 pin all functions

NSN 5945-00-900-4786

Electromagnetic Relay - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300