NSN 5945-00-900-4865

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-900-4865

Overall Length:
1.666 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.390 inches single mounting facility
Overall Height:
1.510 inches
Overall Width:
1.000 inches
Mounting Slot Width:
0.150 inches single mounting facility
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Contact Material:
Silver
Contact Surface Treatment:
Gold
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
Winding Dc Resistance Rating: 150.0 ohms single winding
150.0 ohms single winding
150.0 ohms single winding Duty Type:
150.0 ohms single winding Duty Type: Continuous
150.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity:
150.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 2 slotted hole single mounting facility
150.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 2 slotted hole single mounting facility Storage Type:
150.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 2 slotted hole single mounting facility Storage Type: General purpose warehouse
Duty Type: Continuous Mounting Facility Type And Quantity: 2 slotted hole single mounting facility Storage Type: General purpose warehouse Cubic Measure:
Duty Type: Continuous Mounting Facility Type And Quantity: 2 slotted hole single mounting facility Storage Type: General purpose warehouse Cubic Measure: 2.515 cubic inches
150.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 2 slotted hole single mounting facility Storage Type: General purpose warehouse Cubic Measure: 2.515 cubic inches Mounting Facility Pattern:

80.0 milliamperes dc single winding

Operating Current Rating And Type:

NSN 5945-00-900-4865

Electromagnetic Relay - Page 2 of 2



Time Delay:

0.007 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

26.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load and 10.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Precious Material And Location:

Contacts silver and contact surfaces gold

Precious Material:

Silver and gold

Terminal Type And Quantity:

14 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300