# NSN 5945-00-900-9962

Electromagnetic Relay - Page 1 of 2



Zioonomagnono riolay ir ago ir or z
View Online at https://aerobasegroup.com/nsn/5945-00-900-9962
Thread Class:
2a single mounting facility
Thread Direction:
Right-hand single mounting facility
Thread Length:
0.312 inches single mounting facility
Overall Length:
1.109 inches
Overall Width:
1.593 inches
Case Material:
Plastic
Environmental Protection:
Dustproof
Fragility Factor:
Moderately rugged
Contact Material:
Silver
Contact Surface Treatment:
Gold flash
Frequency In Hertz:
Between 50.0 and 60.0
Winding Quantity:
1
Coil Quantity:
1
Winding Dc Resistance Rating:
3.9 kilohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
1 threaded stud single mounting facility

## **Storage Type:**

General purpose warehouse

# **Cubic Measure:**

1.518 cubic inches

## Thready Qty Per Inch (tpi):

48 single mounting facility

## Thread Size:

0.099 inches single mounting facility

## **Nonpile-up Main Contact Arrangement:**

4 pole, double throw, one position momentary

# NSN 5945-00-900-9962

Electromagnetic Relay - Page 2 of 2



## **Operating Current Rating And Type:**

11.0 milliamperes ac single winding

## **Operating Voltage Rating And Type At Specificationified Temp:**

120.0 volts ac 25 degrees celsius single winding

## Main Contact Load Current Rating At Maximum Rated Voltage:

3.0 amperes ac resistive load and 3.0 amperes dc resistive load

#### **Main Contact Maximum Voltage Rating In Volts:**

120.0 ac and 30.0 dc

## **Energizing Element Power Rating:**

1.2 volts-amperes

#### **Precious Material And Location:**

Contacts silver and contact surfaces gold

**Precious Material:** 

Silver and gold

#### **Thread Series Designator:**

Unc single mounting facility

#### **Terminal Type And Quantity:**

14 tab, solder lug all functions

Shelf Life:

N/a

**Unit Of Measure:** 

-

Demilitarization:

No

Fiig:

A03300