NSN 5945-00-901-1455

Meter Movement Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-901-1455

Terminal Quantity:
5
Terminal Type:
Solder lug
Scale Linearity:
Nonlinear
Case Material:
Metal
Inscription Background Color:
White
Mounting Configuration:
Three 4-40 unc-2a mtg studs spaced 120 degrees apart on a 1.220 in. Radius
Voltage Rating:
125.0 volts
Main Contact Arrangement:
2 pole, single throw, both positions maintained
Main Contact Current Type:
Dc
Main Contact Current Rating:
50.0 milliamperes
Meter Movement Current Type:
Dc
Dc Meter Movement Voltage In Volts:
Meter Movement Voltage In Volts:
Meter Movement Voltage In Volts: Between 24.000 and 125.000
Meter Movement Voltage In Volts: Between 24.000 and 125.000 Meter Movement Current Range:
Meter Movement Voltage In Volts: Between 24.000 and 125.000 Meter Movement Current Range: +5.0/+25.0 microamperes
Meter Movement Voltage In Volts: Between 24.000 and 125.000 Meter Movement Current Range: +5.0/+25.0 microamperes Meter Movement Range Direction:
Meter Movement Voltage In Volts: Between 24.000 and 125.000 Meter Movement Current Range: +5.0/+25.0 microamperes Meter Movement Range Direction: Left to right
Meter Movement Voltage In Volts: Between 24.000 and 125.000 Meter Movement Current Range: +5.0/+25.0 microamperes Meter Movement Range Direction: Left to right Dial Scale Marking Color:
Meter Movement Voltage In Volts: Between 24.000 and 125.000 Meter Movement Current Range: +5.0/+25.0 microamperes Meter Movement Range Direction: Left to right Dial Scale Marking Color: Black
Meter Movement Voltage In Volts: Between 24.000 and 125.000 Meter Movement Current Range: +5.0/+25.0 microamperes Meter Movement Range Direction: Left to right Dial Scale Marking Color: Black Meter Mounting Type:
Meter Movement Voltage In Volts: Between 24.000 and 125.000 Meter Movement Current Range: +5.0/+25.0 microamperes Meter Movement Range Direction: Left to right Dial Scale Marking Color: Black Meter Mounting Type: Flush
Meter Movement Voltage In Volts: Between 24.000 and 125.000 Meter Movement Current Range: +5.0/+25.0 microamperes Meter Movement Range Direction: Left to right Dial Scale Marking Color: Black Meter Mounting Type: Flush Reset Facility Feature:
Meter Movement Voltage In Volts: Between 24.000 and 125.000 Meter Movement Current Range: +5.0/+25.0 microamperes Meter Movement Range Direction: Left to right Dial Scale Marking Color: Black Meter Mounting Type: Flush Reset Facility Feature: Provided
Meter Movement Voltage In Volts: Between 24.000 and 125.000 Meter Movement Current Range: +5.0/+25.0 microamperes Meter Movement Range Direction: Left to right Dial Scale Marking Color: Black Meter Mounting Type: Flush Reset Facility Feature: Provided Lock In Device Type:
Meter Movement Voltage In Volts: Between 24.000 and 125.000 Meter Movement Current Range: +5.0/+25.0 microamperes Meter Movement Range Direction: Left to right Dial Scale Marking Color: Black Meter Mounting Type: Flush Reset Facility Feature: Provided Lock In Device Type: Coil
Meter Movement Voltage In Volts: Between 24.000 and 125.000 Meter Movement Current Range: +5.0/+25.0 microamperes Meter Movement Range Direction: Left to right Dial Scale Marking Color: Black Meter Mounting Type: Flush Reset Facility Feature: Provided Lock In Device Type: Coil Release Method:
Meter Movement Voltage In Volts: Between 24.000 and 125.000 Meter Movement Current Range: +5.0/+25.0 microamperes Meter Movement Range Direction: Left to right Dial Scale Marking Color: Black Meter Mounting Type: Flush Reset Facility Feature: Provided Lock In Device Type: Coil Release Method: Manual

2.210 inches

NSN 5945-00-901-1455

Meter Movement Relay - Page 2 of 2



Meter Depth To Mounting Flange:
1.470 inches
Precious Material And Location:
Contact platinum
Precious Material:
Platinum
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: T142-k