NSN 5945-00-901-2915

Electrical Solenoid - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-901-2915

Thread Class:
2a mounting facility bushing
Body Style:
Cylindrical frame
Thread Length:
0.500 inches mounting facility bushing
Body Diameter:
1.000 inches
Body Length:
2.000 inches
Case Material:
Metal
Case Surface Treatment:
Any acceptable
Maximum Operating Temp:
25.0 degrees celsius
Actuator Diameter:
0.430 inches
Inclosure Type:
Fully enclosed
Magnetic Coil Quantity:
1
Duty Type:
Duty Type:
Duty Type: Intermittent
Duty Type: Intermittent Terminal Location:
Duty Type: Intermittent Terminal Location: End opposite actuator
Duty Type: Intermittent Terminal Location: End opposite actuator Voltage Rating In Volts:
Duty Type: Intermittent Terminal Location: End opposite actuator Voltage Rating In Volts: 28.0 dc
Duty Type: Intermittent Terminal Location: End opposite actuator Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity:
Duty Type: Intermittent Terminal Location: End opposite actuator Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 1 threaded bushing
Duty Type: Intermittent Terminal Location: End opposite actuator Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 1 threaded bushing Current Rating:
Duty Type: Intermittent Terminal Location: End opposite actuator Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 1 threaded bushing Current Rating: 3.0 amperes
Duty Type: Intermittent Terminal Location: End opposite actuator Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 1 threaded bushing Current Rating: 3.0 amperes Thready Qty Per Inch (tpi):
Duty Type: Intermittent Terminal Location: End opposite actuator Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 1 threaded bushing Current Rating: 3.0 amperes Thready Qty Per Inch (tpi): 18 mounting facility bushing
Duty Type: Intermittent Terminal Location: End opposite actuator Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 1 threaded bushing Current Rating: 3.0 amperes Thready Qty Per Inch (tpi): 18 mounting facility bushing Actuator Stroke Type:
Duty Type: Intermittent Terminal Location: End opposite actuator Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 1 threaded bushing Current Rating: 3.0 amperes Thready Qty Per Inch (tpi): 18 mounting facility bushing Actuator Stroke Type: Pull
Duty Type: Intermittent Terminal Location: End opposite actuator Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 1 threaded bushing Current Rating: 3.0 amperes Thready Qty Per Inch (tpi): 18 mounting facility bushing Actuator Stroke Type: Pull Linear Force Delivered:
Duty Type: Intermittent Terminal Location: End opposite actuator Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 1 threaded bushing Current Rating: 3.0 amperes Thready Qty Per Inch (tpi): 18 mounting facility bushing Actuator Stroke Type: Pull Linear Force Delivered: 13.00 pounds

0.030 inches

NSN 5945-00-901-2915

Electrical Solenoid - Page 2 of 2



Tŀ	re	ad	S	ize	•

0.625 inches mounting facility bushing

Thread Series Designator:

Unef mounting facility bushing

Terminal Type And Quantity:

1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A134a0