## NSN 5945-00-902-9016

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-902-9016

Ov	erall Length:
1.3	30 inches
Се	nter To Center Distance Between Mounting Facilities Parallel To Length:
1.0	78 inches single mounting facility
Ov	erall Height:
0.4	00 inches
Ov	erall Width:
0.9	20 inches
En	vironmental Protection:
He	rmetic
Un	threaded Mounting Hole Diameter:
0.1	20 inches single mounting facility
En	d Application:
Ту	pe no. An/tsc-38
Wi	nding Quantity:
1	
Со	il Quantity:
1	
Wi	nding Dc Resistance Rating:
600	0.0 ohms single winding
Du	ty Type:
Со	ntinuous
Мо	ounting Facility Type And Quantity:
2 u	inthreaded hole single mounting facility
Мо	ounting Facility Pattern:
In-	line single mounting facility
No	npile-up Main Contact Arrangement:
2 p	ole, double throw, one position momentary
Tin	ne Delay:
0.0	07 seconds fixed operate and release time
Op	erating Voltage Rating And Type At Specificationified Temp:
26.	5 volts dc 25 degrees celsius single winding
Ма	in Contact Load Current Rating At Maximum Rated Voltage:
2.0	amperes ac resistive load and 3.0 amperes dc resistive load
Ма	in Contact Maximum Voltage Rating In Volts:
11	5.0 ac and 24.0 dc
Te	rminal Type And Quantity:
8 p	in all functions
Sh	elf Life:
N/a	a
Un	it Of Measure:

--

## NSN 5945-00-902-9016

Electromagnetic Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300