# NSN 5945-00-904-7045

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-904-7045

## **Overall Length:**

1.410 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.200 inches single mounting facility

#### Center To Center Distance Between Mounting Facilities Parallel To Width:

0.400 inches single mounting facility

#### **Overall Height:**

1.000 inches

**Overall Width:** 

0.610 inches

**Environmental Protection:** 

Hermetic

**Unthreaded Mounting Hole Diameter:** 

0.096 inches single mounting facility

#### Fragility Factor:

Moderately rugged

## Winding Quantity:

1

## **Purpose For Which Designed:**

General

**Coil Quantity:** 

1

Winding Dc Resistance Rating:

500.0 ohms single winding

**Duty Type:** 

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

#### Storage Type:

General purpose warehouse

**Features Provided:** 

Polarized

**Mounting Facility Pattern:** 

Rectangular single mounting facility

#### Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

### **Operating Current Rating And Type:**

2.0 amperes dc single winding

### Time Delay:

0.006 seconds fixed operate time

## NSN 5945-00-904-7045

Electromagnetic Relay - Page 2 of 2

---



Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes ac resistive load and 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 26.5 dc Terminal Type And Quantity: 14 pin all functions Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A03300