## NSN 5945-00-906-1091

Rotary Relay - Page 1 of 1

No Fiig: T142-s



View Online at https://aerobasegroup.com/nsn/5945-00-906-1091 **Overall Length:** 1.275 inches **Overall Height:** 0.560 inches Overall Width: 0.410 inches Structural Design: Pile-up **Dc Operating Voltage Rating In Volts:** Between 20.0 and 30.0 **Contact Current Type:** Dc **Contact Maximum Voltage Rating In Volts:** 30.0 **Contact Current Rating At Maximum Rated Voltage:** 2.0 amperes resistive **Contact Maximum Rated Current:** 2.0 amperes resistive **Contact Voltage Rating At Maximum Rated Current:** 26.5 **Coil Terminal Quantity:** 2 **Reset Facility Feature:** Not provided **Coil Dc Resistance:** Between 630.0 ohms and 913.0 ohms **Special Features:** Sterminals are 8 solder hooks; hermetically sealed case per mil-r-5757; coil data: maximum pick-up voltage at 25 deg. C. Is 10 volts; dielectric strength is 500 volts from coil to case and across open contacts; operate time: 5 milliseconds at rated voltage and 25 deg. C.; release time: 5 milliseconds atrated voltage and 25 deg. C.; insulation resistance: coil to case 100 megohms min., all other points 1000 megohms min.; ambient temp. Range: -65 to +165 deg. F.; 2 holes 0.120 in. Dia. Shelf Life: N/a **Unit Of Measure:** Demilitarization: