NSN 5945-00-906-4791

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-906-4791

| Overall Length: |
|---------------------------------------------------------------------------|
| 1.350 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.060 inches single mounting facility |
| Overall Height: |
| 1.510 inches |
| Overall Width: |
| 0.390 inches |
| Environmental Protection: |
| Hermetic |
| Unthreaded Mounting Hole Diameter: |
| 0.120 inches single mounting facility |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 2 unthreaded hole single mounting facility |
| Mounting Facility Pattern: |
| In-line single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 2 pole, double throw, one position momentary |
| Operating Current Rating And Type: |
| 60.0 milliamperes dc single winding |
| Time Delay: |
| 10.00 seconds fixed operate time |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 24.0 volts dc 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 1.0 amperes dc resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 26.5 dc |
| Terminal Type And Quantity: |
| 8 pin all functions |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5945-00-906-4791

Electromagnetic Relay - Page 2 of 2



Fiig:

A03300