NSN 5945-00-911-0441

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-911-0441

| · |
|---|
| Thread Class: |
| 2a single mounting facility |
| Overall Length: |
| 0.800 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.412 inches single mounting facility |
| Overall Height: |
| 1.400 inches |
| Overall Width: |
| 0.400 inches |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 8.0 kilohms single winding |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 2 threaded stud single mounting facility |
| Thread Size: |
| 0.112 inches single mounting facility |
| Mounting Facility Pattern: |
| In-line single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 2 pole, double throw, one position momentary |
| Operating Current Rating And Type: |
| 0.0033 microamperes dc single winding |
| Time Delay: |
| 0.005 seconds fixed operate time |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 2.0 amperes ac resistive load and 1.0 amperes dc resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| Thread Series Designator: |
| Unc single mounting facility |
| Terminal Type And Quantity: |
| 8 pin all functions |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5945-00-911-0441

Electromagnetic Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300