## NSN 5945-00-911-6068

Electromagnetic Relay - Page 1 of 2

1.200 inches single mounting facility

Overall Length: 1.415 inches



View Online at https://aerobasegroup.com/nsn/5945-00-911-6068

**Center To Center Distance Between Mounting Facilities Parallel To Length:** 

Center To Center Distance Between Mounting Facilities Parallel To Width:
0.400 inches single mounting facility
Overall Height:
0.906 inches
Overall Width:
0.610 inches
Environmental Protection:
Hermetic
Unthreaded Mounting Hole Diameter:
0.096 inches single mounting facility
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
500.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
4 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Features Provided:
Polarized
Mounting Facility Pattern:
Rectangular single mounting facility
Nonpile-up Main Contact Arrangement:
4 pole, double throw, one position momentary
Time Delay:
0.005 seconds fixed release time
Operating Voltage Rating And Type At Specificationified Temp:
28.0 volts dc 25 degrees celsius single winding

## NSN 5945-00-911-6068

Electromagnetic Relay - Page 2 of 2



## Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac resistive load and 2.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:** 

115.0 ac and 28.0 dc

**Terminal Type And Quantity:** 

14 tab, solder lug all functions

**Specification Or Standard:** 

C376-1 specification sheet

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300