NSN 5945-00-911-8799

Electromagnetic Relay - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5945-00-911-8799 |
|---|
| Overall Length: |
| 1.330 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.062 inches single mounting facility |
| Overall Height: |
| 0.400 inches |
| Overall Width: |
| 1.207 inches |
| Case Material: |
| Metal |
| Environmental Protection: |
| Shock resistant and vibration resistant |
| Unthreaded Mounting Hole Diameter: |
| 0.120 inches single mounting facility |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 22.0 ohms single winding |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 2 unthreaded hole single mounting facility |
| Cubic Measure: |
| 0.642 cubic inches |
| Mounting Facility Pattern: |
| In-line single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 2 pole, double throw, one position momentary |
| Time Delay: |
| 0.005 seconds fixed release time |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 2.7 volts dc 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 1.0 amperes ac resistive load and 2.0 amperes dc resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| Terminal Type And Quantity: |
| 8 wire hook all functions |
| Shelf Life: |

N/a

NSN 5945-00-911-8799

Electromagnetic Relay - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A03300