

View Online at <https://aerobasegroup.com/nsn/5945-00-912-5406>

**Overall Length:**

1.453 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.995 inches single mounting facility and 1.005 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.120 inches single mounting facility and 0.130 inches single mounting facility

**Overall Height:**

Between 1.261 inches and 1.281 inches

**Overall Width:**

Between 0.350 inches and 0.400 inches

**Mounting Slot Width:**

0.091 inches single mounting facility and 0.101 inches single mounting facility

**Environmental Protection:**

Hermetic

**Winding Quantity:**

1

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

4.5 kilohms single winding and 5.5 kilohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

2 slotted hole single mounting facility

**Mounting Facility Pattern:**

Diagonal single mounting facility

**Nonpile-up Main Contact Arrangement:**

2 pole, double throw, one position momentary

**Operating Current Rating And Type:**

6.0 milliamperes dc single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

100.0 milliamperes dc lamp load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Test Data Document:**

81349-mil-r-5757 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

8 wire hook all functions

**Specification Data:**

81349-mil-r-5757/13 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03300