## NSN 5945-00-913-0339

Electromagnetic Relay - Page 1 of 2



| Zioonomagnono reago reag  |
|---|
| View Online at https://aerobasegroup.com/nsn/5945-00-913-0339                   |
| Overall Length:   |
| 1.714 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Length:       |
| 1.396 inches single mounting facility and 1.446 inches single mounting facility |
| Overall Height:   |
| 1.135 inches  |
| Overall Width:  |
| 0.515 inches  |
| Mounting Slot Width:  |
| 0.150 inches single mounting facility   |
| Case Material:  |
| Metal   |
| Environmental Protection:   |
| Hermetic  |
| Fragility Factor:   |
| Moderately rugged   |
| Winding Quantity:   |
| 1   |
| Purpose For Which Designed:   |
| General   |
| Coil Quantity:  |
| 1   |
| Winding Dc Resistance Rating:   |
| 390.0 ohms single winding   |
| Duty Type:  |
| Continuous  |
| Arc Quenching Method:   |
| Air   |
| Mounting Facility Type And Quantity:  |
| 2 slotted hole single mounting facility   |
| Storage Type:   |

General purpose warehouse

**Cubic Measure:** 

1.002 cubic inches

**Mounting Facility Pattern:** 

In-line single mounting facility

**Nonpile-up Main Contact Arrangement:** 

2 pole, double throw, one position momentary

Time Delay:

0.01 seconds fixed operate and release time

**Operating Voltage Rating And Type At Specificationified Temp:** 

26.5 volts dc 25 degrees celsius single winding

## NSN 5945-00-913-0339

Electromagnetic Relay - Page 2 of 2



## Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load and 10.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:** 

115.0 ac and 28.0 dc

**Terminal Type And Quantity:** 

8 wire hook all functions

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A03300