

View Online at <https://aerobasegroup.com/nsn/5945-00-917-2049>

Thread Class:

2b single mounting facility

Overall Length:

Between 1.310 inches and 1.330 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.057 inches single mounting facility and 1.067 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.276 inches single mounting facility and 0.286 inches single mounting facility

Overall Height:

Between 0.460 inches and 0.480 inches

Overall Width:

Between 0.900 inches and 0.920 inches

Case Material:

Metal

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.115 inches single mounting facility and 0.130 inches single mounting facility

Fragility Factor:

Moderately rugged

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

3.0 kilohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

0.564 cubic inches

Thready Qty Per Inch (tpi):

40 single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

0.004 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac resistive load and 2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Terminal Type And Quantity:

8 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300