NSN 5945-00-919-9892

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-919-9892

| Thread Class: |
|--|
| 2a single mounting facility |
| Overall Length: |
| 0.800 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.412 inches single mounting facility |
| Overall Height: |
| 1.540 inches |
| Overall Width: |
| 0.800 inches |
| Environmental Protection: |
| Hermetic Hermetic |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 3 threaded stud single mounting facility |
| Pile-up Main Contact Form Arrangement: |
| 4c |
| Thread Size: |
| 0.112 inches single mounting facility |
| Mounting Facility Pattern: |
| Triangle single mounting facility |
| Operating Current Rating And Type: |
| 100.0 milliamperes dc single winding |
| Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: |
| 0.412 inches single mounting facility |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 28.0 volts dc 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 1.0 amperes ac inductive load and 2.0 amperes dc inductive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| Thread Series Designator: |
| |
| Unc single mounting facility Shelf Life: |
| N/a |
| Unit Of Measure: |
| one of mousure. |

NSN 5945-00-919-9892

Electromagnetic Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300