NSN 5945-00-929-4622

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-929-4622
Overall Length:
5.500 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.880 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.750 inches single mounting facility
Overall Height:
3.090 inches
Overall Width:
3.250 inches
Environmental Protection:
Dustproof
Unthreaded Mounting Hole Diameter:
0.199 inches single mounting facility
Winding Quantity:
1
Coil Quantity:
1
Duty Type:
Continuous
Mounting Facility Type And Quantity:
6 unthreaded hole single mounting facility
Mounting Facility Pattern:
Rectangular single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Time Delay:
10.00 seconds adjustable operate time and 200.00 seconds adjustable operate time
Nonpile-up Auxiliary Contact Arrangement:
1 pole, double throw, one position momentary
Auxiliary Contact Maximum Voltage Rating In Volts:
480.0 ac
Operating Voltage Rating And Type At Specificationified Temp:
96.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
10.0 amperes ac resistive load and 2.5 amperes dc resistive load
Main Contact Maximum Voltage Rating In Volts:
480.0 ac and 110.0 dc
Terminal Type And Quantity:
11 pin all functions
Shalf Life:

N/a

NSN 5945-00-929-4622

Electromagnetic Relay - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A03300