## NSN 5945-00-931-4543

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-931-4543

## **Overall Length:**

1.719 inches

## **Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.865 inches single mounting facility and 0.885 inches single mounting facility

## **Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.740 inches single mounting facility and 0.760 inches single mounting facility

#### **Overall Height:**

1.780 inches

#### **Overall Width:**

Between 0.990 inches and 1.010 inches

#### **Unthreaded Mounting Hole Diameter:**

0.138 inches single mounting facility

#### **Fragility Factor:**

Moderately rugged

#### **Contact Material:**

Silver

## **Winding Quantity:**

## **Purpose For Which Designed:**

General

## **Coil Quantity:**

1

#### Winding Dc Resistance Rating:

259.2 ohms single winding and 316.8 ohms single winding

## **Duty Type:**

Continuous

## **Arc Quenching Method:**

Air

#### **Mounting Facility Type And Quantity:**

4 unthreaded hole single mounting facility

## Storage Type:

General purpose warehouse

## **Mounting Facility Pattern:**

Rectangular single mounting facility

## **Nonpile-up Main Contact Arrangement:**

4 pole, double throw, one position momentary

## Operating Voltage Rating And Type At Specificationified Temp:

24.0 volts dc 25 degrees celsius single winding

## Main Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load and 5.0 amperes dc resistive load

## Main Contact Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

# NSN 5945-00-931-4543

Electromagnetic Relay - Page 2 of 2



_					
μ	rac	IUIIC	Mate	arıal:	•

Silver

**Terminal Type And Quantity:** 

14 tab, solder lug all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300