# NSN 5945-00-931-4543

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-931-4543

#### **Overall Length:**

1.719 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

0.865 inches single mounting facility and 0.885 inches single mounting facility

## Center To Center Distance Between Mounting Facilities Parallel To Width:

0.740 inches single mounting facility and 0.760 inches single mounting facility

#### **Overall Height:**

1.780 inches

#### **Overall Width:**

Between 0.990 inches and 1.010 inches

#### **Unthreaded Mounting Hole Diameter:**

0.138 inches single mounting facility

**Fragility Factor:** 

#### Moderately rugged

**Contact Material:** 

#### Silver

Winding Quantity:

1

## **Purpose For Which Designed:**

General

### **Coil Quantity:**

1

### Winding Dc Resistance Rating:

259.2 ohms single winding and 316.8 ohms single winding

### Duty Type:

Continuous

### Arc Quenching Method:

Air

### Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

### Storage Type:

General purpose warehouse

#### **Mounting Facility Pattern:**

Rectangular single mounting facility

### Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

### Operating Voltage Rating And Type At Specificationified Temp:

24.0 volts dc 25 degrees celsius single winding

#### Main Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load and 5.0 amperes dc resistive load

## Main Contact Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

## NSN 5945-00-931-4543

Electromagnetic Relay - Page 2 of 2



**Precious Material:** 

Silver

Terminal Type And Quantity:

14 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300