## NSN 5945-00-933-3047

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-933-3047

## **Overall Length:**

4.300 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

3.450 inches single mounting facility

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.450 inches single mounting facility

### **Overall Height:**

5.220 inches

#### **Overall Width:**

4.300 inches

## **Unthreaded Mounting Hole Diameter:**

0.250 inches single mounting facility

#### Winding Quantity:

2

#### **Coil Quantity:**

2

## **Duty Type:**

Continuous

## **Mounting Facility Type And Quantity:**

4 unthreaded hole single mounting facility

## **Features Provided:**

Polarized and latching contacts

## **Mounting Facility Pattern:**

Rectangular single mounting facility

## **Nonpile-up Main Contact Arrangement:**

3 pole, double throw, one position momentary

## **Operating Current Rating And Type:**

50.0 milliamperes dc all windings

## Nonpile-up Auxiliary Contact Arrangement:

5 pole, double throw, one position momentary

## **Auxiliary Contact Maximum Voltage Rating In Volts:**

28.0 dc

## **Operating Voltage Rating And Type At Specificationified Temp:**

18.0 volts dc 25 degrees celsius all windings

## Main Contact Load Current Rating At Maximum Rated Voltage:

175.0 milliamperes ac resistive load

## Main Contact Maximum Voltage Rating In Volts:

200.0 ac

## **Terminal Type And Quantity:**

28 pin all functions

### Shelf Life:

N/a

# NSN 5945-00-933-3047

Electromagnetic Relay - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A03300