## NSN 5945-00-933-9308

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-933-9308

view Online at https://aerobasegroup.com/nsn/5945-00-955-9506
Thread Class:
2a single mounting facility
Overall Length:
1.790 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.062 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.933 inches single mounting facility
Overall Height:
2.990 inches
Overall Width:
1.670 inches
Environmental Protection:
Hermetic
Frequency In Hertz:
60.0
Winding Quantity:
1
Coil Quantity:
1
Duty Type:
Continuous
Mounting Facility Type And Quantity:
4 threaded stud single mounting facility
Thread Size:
0.138 inches single mounting facility
Mounting Facility Pattern:
Rectangular single mounting facility
Operating Current Rating And Type:
30.0 milliamperes ac single winding
Time Delay:
3.00 minutes adjustable operate time and 5.00 minutes adjustable operate time
Operating Voltage Rating And Type At Specificationified Temp:
122.0 volts ac 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
2.0 amperes ac resistive load and 5.0 amperes dc resistive load
Mate October 1981 to the William Bud on the William
Main Contact Maximum Voltage Rating In Volts:
115.0 ac and 29.0 dc
115.0 ac and 29.0 dc
115.0 ac and 29.0 dc  Thread Series Designator:

8 pin all functions

## NSN 5945-00-933-9308

Electromagnetic Relay - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300