## NSN 5945-00-934-2617

Electromagnetic Relay - Page 1 of 2

**Overall Length:** 



View Online at https://aerobasegroup.com/nsn/5945-00-934-2617

2.187 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.750 inches single mounting facility
Overall Height:
1.124 inches
Overall Width:
1.490 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Unthreaded Mounting Hole Diameter:
0.147 inches single mounting facility
Fragility Factor:
Moderately rugged
Frequency In Hertz:
60.0
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
3 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
3.662 cubic inches
Mounting Facility Pattern:
Triangle single mounting facility
Nonpile-up Main Contact Arrangement:
4 pole, double throw, one position momentary
Operating Current Rating And Type:
73.0 milliamperes ac single winding
Time Delay:

0.02 seconds fixed operate and release time

## NSN 5945-00-934-2617

Electromagnetic Relay - Page 2 of 2



## Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.844 inches single mounting facility

**Operating Voltage Rating And Type At Specificationified Temp:** 

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

**Terminal Type And Quantity:** 

14 wire hook all functions

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

**Demilitarization:** 

No

Fiig:

A03300