NSN 5945-00-934-2982

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-934-2982

Overall Length: 1.570 inches

Thread Class:

2b single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.062 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.062 inches single mounting facility

Overall Height:

2.620 inches

Overall Width:

1.570 inches

Environmental Protection:

Hermetic

Winding Quantity:

Coil Quantity:

Winding Dc Resistance Rating:

36.0 ohms first winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 threaded hole single mounting facility

Features Provided:

Polarized

Thready Qty Per Inch (tpi):

40 single mounting facility

Thread Size:

0.112 inches single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

0.60 seconds fixed release time

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

3.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

28.0 dc

NSN 5945-00-934-2982

Electromagnetic Relay - Page 2 of 2



Special Features:

A. No. 1 coil controls no. 2 coil capacitor delay. Thus delaying contact transfer by no. 3 coil on drop-out.

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

11 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300