## NSN 5945-00-934-3204

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-934-3204

Overall Le	ength:
------------	--------

5.210 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.000 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:** 

1.812 inches single mounting facility

**Overall Height:** 

1.520 inches

**Overall Width:** 

2.190 inches

**Environmental Protection:** 

Hermetic

**Unthreaded Mounting Hole Diameter:** 

0.173 inches single mounting facility

Winding Quantity:

1

**Coil Quantity:** 

Winding Dc Resistance Rating:

131.0 ohms single winding

**Duty Type:** 

Continuous

**Mounting Facility Type And Quantity:** 

4 unthreaded hole single mounting facility

**Mounting Facility Pattern:** 

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

**Operating Current Rating And Type:** 

21.0 milliamperes dc single winding

Time Delay:

5.00 seconds adjustable operate time and 120.00 seconds adjustable operate time

**Operating Voltage Rating And Type At Specificationified Temp:** 

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

 $1.5 \ \mathrm{amperes} \ \mathrm{ac} \ \mathrm{resistive} \ \mathrm{load} \ \mathrm{and} \ 0.75 \ \mathrm{amperes} \ \mathrm{dc} \ \mathrm{resistive} \ \mathrm{load}$ 

**Main Contact Maximum Voltage Rating In Volts:** 

240.0 ac and 110.0 ac

**Terminal Type And Quantity:** 

8 pin all functions

Shelf Life:

N/a

## NSN 5945-00-934-3204

Electromagnetic Relay - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300