NSN 5945-00-935-5163

Electromagnetic Relay - Page 1 of 2

1.078 inches single mounting facility

Overall Length: 1.320 inches

Overall Height:



View Online at https://aerobasegroup.com/nsn/5945-00-935-5163

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.410 inches
Overall Width:
0.410 inches
Mounting Slot Width:
0.120 inches single mounting facility
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
700.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
2 slotted hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
0.221 cubic inches
Mounting Facility Pattern:
In-line single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Time Delay:
0.004 seconds fixed operate and release time
Operating Voltage Rating And Type At Specificationified Temp:
26.5 volts dc 25 degrees celsius single winding

NSN 5945-00-935-5163

Electromagnetic Relay - Page 2 of 2



Main Contact Load Current Rating At Maximum Rated Voltage:

160.0 milliamperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Test Data Document:

81349-mil-r-5757 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

8 wire hook all functions

Specification Data:

81349-mil-r-5757/10 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300