

View Online at <https://aerobasegroup.com/nsn/5945-00-935-5266>

**Thread Class:**

2a single mounting facility

**Overall Length:**

2.180 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.187 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.187 inches single mounting facility

**Overall Height:**

1.530 inches

**Overall Width:**

1.530 inches

**Environmental Protection:**

Hermetic

**Frequency In Hertz:**

400.0

**Winding Quantity:**

1

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

2.43 kilohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

4 threaded stud single mounting facility

**Thread Size:**

0.138 inches single mounting facility

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:**

4 pole, double throw, one position momentary

**Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts ac 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

10.0 amperes ac resistive load and 6.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Test Data Document:**

81349-mil-r-5757 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unc single mounting facility

**Terminal Type And Quantity:**

14 pin all functions

**Specification Data:**

81349-mil-r-5757/10 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300