NSN 5945-00-938-5390

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-938-5390

| Overall Length: |
|---|
| 5.750 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 4.000 inches single mounting facility |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 4.000 inches single mounting facility |
| Overall Height: |
| 3.625 inches |
| Overall Width: |
| 5.750 inches |
| Case Material: |
| Steel, corrosion resisting |
| Environmental Protection: |
| Dustproof |
| Unthreaded Mounting Hole Diameter: |
| 0.188 inches single mounting facility |
| Contact Material: |
| Silver |
| Frequency In Hertz: |
| 50.0 or 60.0 |
| Winding Quantity: |
| 3 |
| Coil Quantity: |
| 3 |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole single mounting facility |
| Features Provided: |
| Latching contacts |
| Mounting Facility Pattern: |
| Rectangular single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 2 pole, single throw, normally open, momentary action |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 115.0 volts ac 25 degrees celsius all windings |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 5.0 amperes ac resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 230.0 ac |
| Special Features: |

Two common coil terminals

NSN 5945-00-938-5390

Electromagnetic Relay - Page 2 of 2



| Precious Material And Location: |
|---------------------------------|
| Contact silver |
| Precious Material: |
| Silver |
| Terminal Type And Quantity: |
| 8 threaded stud all functions |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A03300