## NSN 5945-00-939-5842

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-939-5842

| Overall Length:  |
|--|
| 5.000 inches   |
| Overall Height:  |
| 4.120 inches   |
| Overall Width:   |
| 4.250 inches   |
| Mounting Slot Width:   |
| 0.203 inches single mounting facility  |
| Environmental Protection:  |
| Water resistant  |
| Winding Quantity:  |
| 1  |
| Coil Quantity:   |
| 1  |
| Winding Dc Resistance Rating:  |
| 568.0 ohms single winding  |
| Duty Type:   |
| Continuous   |
| Arc Quenching Method:  |
| Capacitor  |
| Mounting Facility Type And Quantity:   |
| 3 slotted hole single mounting facility  |
| Pile-up Main Contact Form Arrangement:   |
| 3a3a1b1c   |
| Mounting Facility Pattern:   |
| Triangle single mounting facility  |
| Operating Current Rating And Type:   |
| 4.8 amperes dc single winding  |
| Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: |
| 4.625 inches single mounting facility  |
| Operating Voltage Rating And Type At Specificationified Temp:  |
| 30.0 volts dc 25 degrees celsius single winding  |
| Main Contact Load Current Rating At Maximum Rated Voltage:   |
| 75.0 amperes ac resistive load and 75.0 amperes dc resistive load  |
| Main Contact Maximum Voltage Rating In Volts:  |
| 250.0 ac and 28.0 dc   |
| Terminal Type And Quantity:  |
| 19 pin all functions   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |

--

## NSN 5945-00-939-5842

Electromagnetic Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300