## NSN 5945-00-944-2443

Electrical Solenoid - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-944-2443

| Thread Class:   |
|---|
| 2a mounting facility stud   |
| Body Style:   |
| Base end actuator   |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.875 inches  |
| Body Diameter:  |
| 1.344 inches  |
| Body Height:  |
| 0.875 inches  |
| Case Material:  |
| Steel   |
| Maximum Operating Temp:   |
| 65.0 degrees celsius  |
| Actuator Diameter:  |
| 0.250 inches  |
| Inclosure Type:   |
| Fully enclosed  |
| Magnetic Coil Quantity:   |
| 1   |
| Electrical Resistance:  |
| 4.67 ohms   |
| Duty Type:  |
| Continuous  |
| Terminal Location:  |
| Base edge   |
| Voltage Rating In Volts:  |
| 30.0 dc   |
| Mounting Facility Type And Quantity:                                      |
| 2 threaded stud   |
| Torque Rating And Type:   |
| 0.43 inch-pounds end  |
| Thready Qty Per Inch (tpi):   |
| 32 mounting facility stud   |
| Actuator Stroke Type:   |
| Rotary  |
| Power Takeoff Connection Type:  |
| Flatted-drilled   |
| Thread Size:  |
| 0.138 inches mounting facility stud                                       |
| Mounting Facility Pattern:  |

Two position in-line

## NSN 5945-00-944-2443

Electrical Solenoid - Page 2 of 2



20.0 clockwise

**Thread Series Designator:** 

Unc mounting facility stud

**Terminal Type And Quantity:** 

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

\_\_\_

Demilitarization:

No

Fiig:

A134a0