

View Online at <https://aerobasegroup.com/nsn/5945-00-944-5299>

Thread Class:

2a single mounting facility

Overall Length:

1.660 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.938 inches single mounting facility

Overall Height:

2.357 inches

Overall Width:

1.420 inches

Environmental Protection:

Hermetic

Frequency In Hertz:

60.0 or 400.0

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

1170.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

3 threaded stud single mounting facility

Features Provided:

Polarized

Thread Size:

0.138 inches single mounting facility

Mounting Facility Pattern:

Triangle single mounting facility

Nonpile-up Main Contact Arrangement:

1 two circuit, double break/double make, one position momentary

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.187 inches single mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

50.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

15.0 amperes ac resistive load and 25.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Special Features:

Must be derated to 10.0 amp if used as spdt

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

6 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300