# NSN 5945-00-945-9650

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-945-9650

## **Overall Length:**

1.410 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.200 inches single mounting facility

#### Center To Center Distance Between Mounting Facilities Parallel To Width:

0.400 inches single mounting facility

#### **Overall Height:**

0.640 inches

**Overall Width:** 

0.810 inches

**Environmental Protection:** 

Hermetic

**Unthreaded Mounting Hole Diameter:** 

0.096 inches single mounting facility

#### Fragility Factor:

Moderately rugged

## Winding Quantity:

1

#### **Purpose For Which Designed:**

General

#### **Coil Quantity:**

1

#### Winding Dc Resistance Rating:

1.132 kilohms single winding

#### Duty Type:

Continuous

#### Arc Quenching Method:

Air

## Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

## Storage Type:

General purpose warehouse

## Mounting Facility Pattern:

Rectangular single mounting facility

## Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

## Operating Current Rating And Type:

0.01 amperes dc single winding

#### Time Delay:

0.006 seconds fixed operate time

# Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac resistive load and 2.0 amperes dc resistive load

NSN 5945-00-945-9650

Electromagnetic Relay - Page 2 of 2



Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

### Terminal Type And Quantity:

14 pin all functions

Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A03300