

View Online at <https://aerobasegroup.com/nsn/5945-00-946-6803>

Overall Length:

1.453 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.005 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.130 inches single mounting facility

Overall Height:

1.491 inches

Overall Width:

Between 0.350 inches and 0.400 inches

Mounting Slot Width:

0.110 inches single mounting facility

Environmental Protection:

Hermetic and shock resistant and vibration resistant

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

10.0 kilohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

2 slotted hole single mounting facility

Mounting Facility Pattern:

Diagonal single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Current Rating And Type:

4.0 milliamperes dc single winding

Time Delay:

0.015 seconds fixed operate time

Main Contact Load Current Rating At Maximum Rated Voltage:

100.0 milliamperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Test Data Document:

81349-mil-r-5757 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

8 wire hook all functions

Specification Data:

81349-mil-r-5757/13 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300