## NSN 5945-00-947-9448

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-947-9448

view Online at https://acrobasegroup.com/nsi//0545-00-547-5440
Thread Class:
2b single mounting facility
Thread Direction:
Right-hand single mounting facility
Overall Length:
2.000 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.312 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.500 inches single mounting facility
Overall Height:
2.312 inches
Overall Width:
1.812 inches
Case Material:
Metal
Contact Material:
Silver
Contact Surface Treatment:
Gold flash
Frequency In Hertz:
60.0
Winding Quantity:
1
Coil Quantity:
1
Duty Type:
Continuous
Mounting Facility Type And Quantity:
4 threaded hole single mounting facility
Cubic Measure:
8.378 cubic inches
Thready Qty Per Inch (tpi):
32 single mounting facility
Thread Size:
0.138 inches single mounting facility
Mounting Facility Pattern:
Rectangular single mounting facility
Nonpile-up Main Contact Arrangement:
5 pole, double throw, one position momentary
Time Delays

Time Delay:

0.035 seconds fixed operate time

## NSN 5945-00-947-9448

Electromagnetic Relay - Page 2 of 2



## Operating Voltage Rating And Type At Specificationified Temp: 6.0 volts ac 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 20.0 amperes ac resistive load **Main Contact Maximum Voltage Rating In Volts:** 120.0 ac **Precious Material And Location:** Contacts silver and contact surfaces gold **Precious Material:** Silver and gold **Thread Series Designator:** Unc single mounting facility **Terminal Type And Quantity:** 17 screw all functions Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig: A03300