NSN 5945-00-949-1126

Electromagnetic Relay - Page 1 of 2



Electromagnetic Relay - Page 1 of 2	
View Online at https://aerobasegroup.com/nsn/5945-00-949-1126	
Overall Length:	
1.453 inches	
Center To Center Distance Between Mounting Facilities Parallel To Length:	
1.067 inches single mounting facility	
Overall Height:	
1.491 inches	
Overall Width:	
0.400 inches	
Mounting Slot Width:	
0.110 inches single mounting facility	
Case Material:	
Metal	
Environmental Protection:	
Hermetic	
Fragility Factor:	
Moderately rugged	
Winding Quantity:	
1	
Coil Quantity:	
1	
Winding Dc Resistance Rating:	
500.0 ohms single winding	
Duty Type:	
Continuous	
Arc Quenching Method:	
Air	
Mounting Facility Type And Quantity:	
2 slotted hole single mounting facility	

Storage Type:

General purpose warehouse

Cubic Measure:

0.866 cubic inches

Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Current Rating And Type:

18.0 milliamperes dc single winding

Time Delay:

0.01 seconds fixed operate and release time

Main Contact Load Current Rating At Maximum Rated Voltage:

100.0 milliamperes dc lamp load

NSN 5945-00-949-1126

Electromagnetic Relay - Page 2 of 2



Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Test Data Document:

81349-mil-r-5757 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

8 wire hook all functions

Specification Data:

81349-mil-r-5757/13 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300