NSN 5945-00-949-4712

Electromagnetic Relay - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5945-00-949-4712

| Overall Length: |
|---|
| 2.500 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.206 inches single mounting facility |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.017 inches single mounting facility |
| Overall Height: |
| 1.590 inches |
| Overall Width: |
| 2.420 inches |
| Environmental Protection: |
| Dustproof |
| Unthreaded Mounting Hole Diameter: |
| 0.144 inches single mounting facility |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole single mounting facility |
| Features Provided: |
| Polarized |
| Mounting Facility Pattern: |
| Rectangular single mounting facility |
| Time Delay: |
| 25.0000 seconds fixed operate time |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 28.0 volts dc 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 10.0 amperes dc inductive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 28.0 dc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A03300