## NSN 5945-00-949-4940

Electromagnetic Relay - Page 1 of 2

1.200 inches single mounting facility

0.400 inches single mounting facility

2.0 amperes ac inductive load

115.0 ac and 28.0 dc

Main Contact Maximum Voltage Rating In Volts:

Overall Length: 1.410 inches



View Online at https://aerobasegroup.com/nsn/5945-00-949-4940

**Center To Center Distance Between Mounting Facilities Parallel To Length:** 

**Center To Center Distance Between Mounting Facilities Parallel To Width:** 

Overall Height:						
0.610 inches						
Overall Width:						
1.020 inches						
Environmental Protection:						
Hermetic						
Unthreaded Mounting Hole Diameter:						
0.096 inches single mounting facility						
Fragility Factor:						
Moderately rugged						
Winding Quantity:						
1						
Purpose For Which Designed:						
General						
Coil Quantity:						
1						
Winding Dc Resistance Rating:						
500.0 ohms single winding						
Duty Type:						
Continuous						
Arc Quenching Method:						
Air						
Mounting Facility Type And Quantity:						
4 unthreaded hole single mounting facility						
Storage Type:						
General purpose warehouse						
Mounting Facility Pattern:						
Rectangular single mounting facility						
Nonpile-up Main Contact Arrangement:						
4 pole, double throw, one position momentary						
Time Delay:						
0.006 seconds fixed operate time						
Main Contact Load Current Rating At Maximum Rated Voltage:						

## NSN 5945-00-949-4940

Electromagnetic Relay - Page 2 of 2



ī	ermina	ı	Type	Δnd	Qua	antity.
ı	CHILLING	41	INDE	Allu	wu	aiititv.

14 pin all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300