## NSN 5945-00-949-5030

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-949-5030

## **Overall Length:**

10.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.875 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:** 

4.125 inches single mounting facility

**Overall Height:** 

4.000 inches

**Overall Width:** 

8.000 inches

**Unthreaded Mounting Hole Diameter:** 

0.190 inches single mounting facility

Frequency In Hertz:

60.0

Winding Quantity:

**Coil Quantity:** 

Winding Dc Resistance Rating:

95.0 ohms single winding

**Duty Type:** 

Continuous

**Mounting Facility Type And Quantity:** 

4 unthreaded hole single mounting facility

**Mounting Facility Pattern:** 

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:** 

4 pole, single throw, normally open, momentary action

**Operating Current Rating And Type:** 

120.0 milliamperes ac single winding

**Nonpile-up Auxiliary Contact Arrangement:** 

4 pole, single throw, normally closed, momentary action

**Auxiliary Contact Maximum Voltage Rating In Volts:** 

230.0 dc

**Operating Voltage Rating And Type At Specificationified Temp:** 

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

30.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac

**Terminal Type And Quantity:** 

18 pin all functions

## NSN 5945-00-949-5030

Electromagnetic Relay - Page 2 of 2



Fsc Application Data (non-c
-----------------------------

Except engine

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300