NSN 5945-00-950-6874

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-950-6874

| Overall Length: |
|---|
| 1.450 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.200 inches single mounting facility |
| Overall Height: |
| 1.370 inches |
| Overall Width: |
| 0.410 inches |
| Environmental Protection: |
| Hermetic |
| Unthreaded Mounting Hole Diameter: |
| 0.125 inches single mounting facility |
| Frequency In Hertz: |
| Between 60.0 and 400.0 |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 1.0 kilohms single winding |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 2 unthreaded hole single mounting facility |
| Pile-up Main Contact Form Arrangement: |
| 2c |
| Mounting Facility Pattern: |
| In-line single mounting facility |
| Operating Current Rating And Type: |
| 10.0 milliamperes ac single winding |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 120.0 volts ac 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 2.0 amperes ac resistive load and 2.0 amperes dc resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 30.0 ac and 30.0 dc |
| Terminal Type And Quantity: |
| 8 pin all functions |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

NSN 5945-00-950-6874

Electromagnetic Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300