NSN 5945-00-951-5453

Electromagnetic Relay - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5945-00-951-5453

| Thread Class: |
|--|
| 2a single mounting facility |
| Overall Length: |
| 2.270 inches |
| Overall Height: |
| 1.660 inches |
| Overall Width: |
| 1.470 inches |
| Environmental Protection: |
| Hermetic |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 2.8 kilohms single winding |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 3 threaded stud single mounting facility |
| Thread Size: |
| 0.138 inches single mounting facility |
| Mounting Facility Pattern: |
| Triangle single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 1 pole, single throw, normally open, momentary action |
| Time Delay: |
| 0.40 seconds fixed release time |
| Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: |
| 1.187 inches single mounting facility |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 70.0 volts dc 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 300.0 milliamperes ac resistive load and 300.0 milliamperes dc resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 115.0 ac and 27.5 dc |
| Thread Series Designator: |
| Unc single mounting facility |
| Terminal Type And Quantity: |
| 4 pin all functions |
| Shelf Life: |

NSN 5945-00-951-5453

Electromagnetic Relay - Page 2 of 2



| | Of | | | |
|--|----|--|--|--|

--

Demilitarization:

No

Fiig:

A03300