## NSN 5945-00-951-5723

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-951-5723

| Thread Class:  |  |  |
|--|--|--|
| 2a single mounting facility  |  |  |
| Thread Direction:  |  |  |
| Right-hand single mounting facility  |  |  |
| Overall Length:  |  |  |
| 1.650 inches   |  |  |
| Center To Center Distance Between Mounting Facilities Parallel To Width:                                 |  |  |
| 0.938 inches single mounting facility  |  |  |
| Overall Height:  |  |  |
| 2.906 inches   |  |  |
| Overall Width:   |  |  |
| 1.440 inches   |  |  |
| Environmental Protection:  |  |  |
| Dustproof  |  |  |
| Winding Quantity:  |  |  |
| 2  |  |  |
| Coil Quantity:   |  |  |
| 2  |  |  |
| Duty Type:   |  |  |
| Continuous   |  |  |
| Mounting Facility Type And Quantity:   |  |  |
| 3 threaded stud single mounting facility   |  |  |
| Features Provided:   |  |  |
| Polarized  |  |  |
| Thready Qty Per Inch (tpi):  |  |  |
| 32 single mounting facility  |  |  |
| Thread Size:   |  |  |
| 0.138 inches single mounting facility  |  |  |
| Mounting Facility Pattern:   |  |  |
| Triangle single mounting facility  |  |  |
| Nonpile-up Main Contact Arrangement:   |  |  |
| 4 pole, double throw, one position momentary   |  |  |
| Time Delay:  |  |  |
| 1.00 seconds adjustable operate time and 10.00 seconds adjustable operate time                           |  |  |
| Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: |  |  |
| 1.187 inches single mounting facility  |  |  |
| Operating Voltage Rating And Type At Specificationified Temp:  |  |  |
| 30.0 volts dc 25 degrees celsius all windings  |  |  |
| Main Contact Load Current Rating At Maximum Rated Voltage:   |  |  |
| 5.0 amperes ac resistive load and 5.0 amperes dc resistive load  |  |  |
| Main Contact Maximum Voltage Rating In Volts:  |  |  |

115.0 ac and 28.0 dc

## NSN 5945-00-951-5723

Electromagnetic Relay - Page 2 of 2



| Special | Features: |
|---------|-----------|
|---------|-----------|

Extra spdt contact arrangement in line with coils

**Thread Series Designator:** 

Unc single mounting facility

**Terminal Type And Quantity:** 

14 wire hook all functions

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A03300