# NSN 5945-00-952-2300

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-952-2300

#### **Thread Class:**

2a single mounting facility

#### **Overall Length:**

1.340 inches

# **Overall Height:**

2.000 inches

#### **Overall Width:**

0.950 inches

#### **Environmental Protection:**

Hermetic

#### Winding Quantity:

1

## Coil Quantity:

1

#### Winding Dc Resistance Rating:

700.0 ohms single winding

**Duty Type:** 

Continuous

## Mounting Facility Type And Quantity:

3 threaded stud single mounting facility

## Thread Size:

0.112 inches single mounting facility

## Mounting Facility Pattern:

Triangle single mounting facility

#### Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

#### **Operating Current Rating And Type:**

30.0 milliamperes dc single winding

#### Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.000 inches single mounting facility

# Operating Voltage Rating And Type At Specificationified Temp:

24.0 volts dc 25 degrees celsius single winding

# Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac resistive load and 2.0 amperes dc resistive load

# Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 29.0 dc

# Thread Series Designator:

Unc single mounting facility

# Terminal Type And Quantity:

14 pin all functions

# Fsc Application Data (non-core):

Relay, armature, except engine

# NSN 5945-00-952-2300

Electromagnetic Relay - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A03300

