# NSN 5945-00-952-9484

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-952-9484

## Overall Length:

1.410 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.200 inches single mounting facility

#### Center To Center Distance Between Mounting Facilities Parallel To Width:

0.400 inches single mounting facility

#### **Overall Height:**

1.000 inches

**Overall Width:** 

0.610 inches

**Environmental Protection:** 

Hermetic

**Unthreaded Mounting Hole Diameter:** 

0.096 inches single mounting facility

#### **Fragility Factor:**

Moderately rugged

## Winding Quantity:

1

### **Purpose For Which Designed:**

General

**Coil Quantity:** 

1

### Winding Dc Resistance Rating:

500.0 ohms single winding

**Duty Type:** 

Continuous

#### Arc Quenching Method:

Air

## Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

## Storage Type:

General purpose warehouse

## Mounting Facility Pattern:

Rectangular single mounting facility

## Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

## Operating Current Rating And Type:

2.0 amperes dc single winding

## Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

## Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac resistive load and 2.0 amperes dc resistive load

# NSN 5945-00-952-9484

Electromagnetic Relay - Page 2 of 2



Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Terminal Type And Quantity:

14 pin all functions

Fsc Application Data (non-core):

Relay, armature, except engine

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A03300