## NSN 5945-00-956-7676

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-956-7676

| g   |
|---|
| Overall Length:   |
| 1.180 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.000 inches single mounting facility                                     |
| Overall Height:   |
| 0.400 inches  |
| Overall Width:  |
| 1.125 inches  |
| Environmental Protection:   |
| Hermetic  |
| Unthreaded Mounting Hole Diameter:  |
| 0.096 inches single mounting facility                                     |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| 0.125 inches single mounting facility                                     |
| Winding Quantity:   |
| 1   |
| Coil Quantity:  |
| 1   |
| Winding Dc Resistance Rating:   |
| 2.0 kilohms single winding and 2.75 kilohms single winding                |
| Duty Type:  |
| Continuous  |
| Mounting Facility Type And Quantity:                                      |
| 4 unthreaded hole single mounting facility                                |
| Mounting Facility Pattern:  |
| Rectangular single mounting facility                                      |
| Nonpile-up Main Contact Arrangement:                                      |
| 2 pole, double throw, one position momentary                              |
| Time Delay:   |
| 0.006 seconds fixed release time  |
| Operating Voltage Rating And Type At Specificationified Temp:             |
| 50.0 volts dc 25 degrees celsius single winding                           |
| Main Contact Load Current Rating At Maximum Rated Voltage:                |
| 1.0 amperes ac resistive load and 2.0 amperes dc resistive load           |
| Main Contact Maximum Voltage Rating In Volts:                             |
| 115.0 ac and 28.0 dc  |
| Terminal Type And Quantity:   |
| 8 pin all functions   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |

--

## NSN 5945-00-956-7676

Electromagnetic Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300