NSN 5945-00-958-6409

Meter Movement Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-958-6409

| Terminal Quantity: |
|---|
| 4 |
| Terminal Type: |
| Threaded stud |
| Scale Unit Of Measure Inscription: |
| Milliamperes |
| Scale Division Quantity: |
| 50 |
| Mounting Flange Length: |
| 2.656 inches |
| Mounting Flange Width: |
| 2.468 inches |
| Case Material: |
| Plastic |
| Environmental Protection: |
| Dustproof |
| End Application: |
| Very high frequency omnirange/tacan (vortac) |
| Mounting Configuration: |
| Four no. 4-40 thd studs spaced 1.8 in. C to c |
| Voltage Rating: |
| 125.0 volts |
| Scale Measurement Range: |
| +0.0/+1.0 |
| Main Contact Arrangement: |
| 1 pole, single throw, normally open, momentary action |
| Main Contact Current Type: |
| Dc |
| Main Contact Current Rating: |
| 25.0 milliamperes |
| Meter Movement Current Type: |
| Dc |
| Meter Movement Voltage In Volts: |
| Between 5.000 and 25.000 |
| Meter Movement Current Range: |
| +0.0/+1.0 milliamperes |
| Meter Movement Range Direction: |
| Left to right |
| Dial Scale Marking Color: |
| Black |
| Meter Mounting Type: |
| Flush |

Flush

NSN 5945-00-958-6409

Meter Movement Relay - Page 2 of 2



| Contact Closing Condition: |
|-----------------------------------|
| Increase value |
| Reset Facility Feature: |
| Provided |
| Lock In Device Type: |
| Coil |
| Release Method: |
| Manual |
| Meter Body Diameter: |
| 2.218 inches |
| Meter Depth To Mounting Flange: |
| 1.125 inches |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| |