

View Online at <https://aerobasegroup.com/nsn/5945-00-959-9524>

**Overall Length:**

Between 4.970 inches and 5.030 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

4.500 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.313 inches single mounting facility

**Overall Height:**

Between 2.750 inches and 2.810 inches

**Overall Width:**

Between 2.780 inches and 2.840 inches

**Environmental Protection:**

Dustproof

**Unthreaded Mounting Hole Diameter:**

0.188 inches single mounting facility and 0.206 inches single mounting facility

**Fragility Factor:**

Moderately rugged

**Winding Quantity:**

1

**Purpose For Which Designed:**

General

**Coil Quantity:**

1

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

4 unthreaded hole single mounting facility

**Storage Type:**

General purpose warehouse

**Cubic Measure:**

40.141 cubic inches

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:**

2 pole, single throw, normally open, momentary action

**Nonpile-up Auxiliary Contact Arrangement:**

2 pole, single throw, normally open, momentary action

**Auxiliary Contact Maximum Voltage Rating In Volts:**

29.0 dc

**Operating Voltage Rating And Type At Specificationified Temp:**

29.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

50.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

29.0 dc

**Auxiliary Contact Load Current Rating At Maximum Rated Voltage:**

5.0 amperes dc resistive load

**Terminal Type And Quantity:**

12 threaded stud all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300