NSN 5945-00-959-9524

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-959-9524

Overall Length:

Between 4.970 inches and 5.030 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.500 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.313 inches single mounting facility

Overall Height:

Between 2.750 inches and 2.810 inches

Overall Width:

Between 2.780 inches and 2.840 inches

Environmental Protection:

Dustproof

Unthreaded Mounting Hole Diameter:

0.188 inches single mounting facility and 0.206 inches single mounting facility

Fragility Factor:

Moderately rugged

Winding Quantity:

Purpose For Which Designed:

General

Coil Quantity:

1

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

40.141 cubic inches

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, single throw, normally open, momentary action

Nonpile-up Auxiliary Contact Arrangement:

2 pole, single throw, normally open, momentary action

Auxiliary Contact Maximum Voltage Rating In Volts:

29.0 dc

Operating Voltage Rating And Type At Specificationified Temp:

29.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

50.0 amperes dc resistive load

NSN 5945-00-959-9524

Electromagnetic Relay - Page 2 of 2

Fiig: A03300



main Contact maximum voltage Rating in volts:
29.0 dc
Auxiliary Contact Load Current Rating At Maximum Rated Voltage:
5.0 amperes dc resistive load
Terminal Type And Quantity:
12 threaded stud all functions
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No