NSN 5945-00-966-4567

Electromagnetic Relay - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5945-00-966-4567

Overall Length:
0.800 inches
Overall Height:
0.900 inches
Overall Width:
0.400 inches
Environmental Protection:
Hermetic
Unthreaded Mounting Hole Diameter:
0.096 inches single mounting facility
Winding Quantity:
1
Coil Quantity:
1
Winding Dc Resistance Rating:
750.0 ohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
1 unthreaded hole single mounting facility
Pile-up Main Contact Form Arrangement:
2c
Features Provided:
Polarized
Operating Current Rating And Type:
Operating Current Rating And Type: 30.0 milliamperes dc single winding
30.0 milliamperes dc single winding
30.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp:
 30.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding
 30.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage:
 30.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes ac resistive load and 2.0 amperes dc resistive load
 30.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes ac resistive load and 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 115.0 dc
 30.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes ac resistive load and 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 115.0 dc Terminal Type And Quantity:
 30.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes ac resistive load and 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 115.0 dc Terminal Type And Quantity: 8 pin all functions
 30.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes ac resistive load and 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 115.0 dc Terminal Type And Quantity: 8 pin all functions Shelf Life:
30.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes ac resistive load and 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 115.0 dc Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a
 30.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes ac resistive load and 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 115.0 dc Terminal Type And Quantity: 8 pin all functions Shelf Life:
30.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes ac resistive load and 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 115.0 dc Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a Unit Of Measure:
30.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes ac resistive load and 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 115.0 dc Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a Unit Of Measure: Demilitarization:
30.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes ac resistive load and 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 115.0 dc Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a Unit Of Measure: Demilitarization: No
30.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes ac resistive load and 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 115.0 dc Terminal Type And Quantity: 8 pin all functions Shelf Life: N/a Unit Of Measure: Demilitarization: