## NSN 5945-00-969-5642

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-969-5642

**Thread Class:** 2a single mounting facility **Overall Length:** 1.340 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.500 inches single mounting facility Center To Center Distance Between Mounting Facilities Parallel To Width: 1.500 inches single mounting facility **Overall Height:** 3.630 inches **Overall Width:** 0.960 inches **Environmental Protection:** Hermetic Winding Quantity: **Coil Quantity:** Winding Dc Resistance Rating: 150.0 ohms single winding **Duty Type:** Continuous **Mounting Facility Type And Quantity:** 4 threaded stud single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.164 inches single mounting facility **Mounting Facility Pattern:** Rectangular single mounting facility **Operating Current Rating And Type:** 170.0 milliamperes dc single winding Time Delay: 0.01 seconds adjustable release time and 0.02 seconds adjustable release time **Operating Voltage Rating And Type At Specificationified Temp:** 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 12.0 amperes ac resistive load and 15.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 120.0 dc

**Thread Series Designator:** 

Unc single mounting facility

## NSN 5945-00-969-5642

Electromagnetic Relay - Page 2 of 2



	Fsc /	Αp	plication	Data (	(non-core)	):
--	-------	----	-----------	--------	------------	----

Relay armature, except engine

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300