

View Online at <https://aerobasegroup.com/nsn/5945-00-969-5642>

Thread Class:

2a single mounting facility

Overall Length:

1.340 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.500 inches single mounting facility

Overall Height:

3.630 inches

Overall Width:

0.960 inches

Environmental Protection:

Hermetic

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

150.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 threaded stud single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.164 inches single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Operating Current Rating And Type:

170.0 milliamperes dc single winding

Time Delay:

0.01 seconds adjustable release time and 0.02 seconds adjustable release time

Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

12.0 amperes ac resistive load and 15.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 120.0 dc

Thread Series Designator:

Unc single mounting facility

Fsc Application Data (non-core):

Relay armature, except engine

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300